

NORDIC RACING OIL 10W/60

Fully Synthetic Passenger Car Motor Oil

NORDIC RACING OIL 10W/60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

NORDIC RACING OIL 10W/60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

NORDIC RACING OIL 10W/60 exceeds the following performance criteria:

API SN/CF

ACEA A3/B4

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-60
Density @15°C	kg/m ³	ASTM D4052	848
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	16
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	23.9
Viscosity Index		ASTM D2270	177
Viscosity CCS @ -25°C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-45
Total Base Number	mgKOH/g	ASTM D2896	10.
Sulphated Ash	%Wt	ASTM D874	1.09

Date Issued: 13-03-2018

Supersedes: 30-05-2017

Revision Nr.: 1

Nordic Lube ApS, Udsigten 19, 3500 Vaerleose, Denmark

www.nordic-lube.com