

NORDIC VECTRO 0W/30 V

Fully Synthetic Passenger Car Motor Oil

NORDIC VECTRO 0W/30 V is a fuel saving oil based on 100% synthetic technology specially designed for use in petrol- and diesel-powered Volvo passenger cars with or without turbocharger where Volvo VCC 95200377 is required.

NORDIC VECTRO 0W/30 V is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Protection to wear by cold start.
- Very good low temperature properties.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Added fuel economy

NORDIC VECTRO 0W/30 V exceeds the following performance criteria:

Approved Volvo VCC 95200377

Meets ACEA A5/B5 API: SL

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W/30
Density @15°C	kg/m ³	ASTM D4052	843
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	51
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.6
Viscosity Index		ASTM D2270	165
Viscosity CCS @-35°, max.	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-42

Date Issued: 14-06-2021

Supersedes:

Revision Nr.: 1