

NORDIC VECTRO 10W/30 SN

Semi Synthetic Passenger Car Motor Oil

NORDIC VECTRO 10W/30 SN is a high-performance fuel saving engine oil based on synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans.

NORDIC VECTRO 10W/30 SN is based on synthetic technology base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

NORDIC VECTRO 10W/30 SN exceeds the following performance criteria:

API SN/CF	ACEA A3/B4	MB 229.3	VW 501.01/505.00
RN 0700/0710	PSA B71 2300		

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W/30
Density @15°C	kg/m ³	ASTM D4052	867
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	74.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.9
Viscosity Index		ASTM D2270	165
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.3
Sulphated Ash	%Wt	ASTM D874	1.31

Date Issued: 14-06-2021

Supersedes:

Revision Nr.: 1