

## NORDIC FUELTEC 5W/30 SN/CF

### Semi-Synthetic Passenger Car Motor Oil

**NORDIC FUELTEC 5W/30 SN/CF** is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Partide Filter (DPF).

**NORDIC FUELTEC 5W/30 SN/CF** is formulated with high quality mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

**NORDIC FUELTEC 5W/30 SN/CF** exceeds the following performance criteria:

API SN

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	5W/30
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	867
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	70
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.8
Viscosity Index		ASTM D2270	14
Viscosity CCS @-30°, max.	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-36
Total Base Number	mgKOH/g	ASTM D2896	6.8

Date Issued: 29-05-2021

Supersedes:

Revision Nr.: 1

Nordic Lube ApS, Udsigten 19, 3500 Vaerlose, Denmark

[www.nordic-lube.com](http://www.nordic-lube.com)