

NORDIC EVOTECH 5W/30 LL

Fully Synthetic MID SAPS Passenger Car Motor Oil

NORDIC EVOTECH 5W/30 LL is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

NORDIC EVOTECH 5W/30 LL is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with modern catalysts.

Specifications, recommendations and approvals:

ACEA	C3	Porsche	C30
ACEA	Recommended for ACEA C2	Renault	RN 0700
API	SP	Renault	RN 0710
BMW	Longlife-04(B48)	VAG	VW 501.01
BMW	Longlife-19 FE	VAG	VW 502.00
Chrysler	MS-11106	VAG	VW 503.00
GM	Dexos2	VAG	VW 503.01
MB	229.31	VAG	VW 504.00 Baumuster 2020
MB	229.51	VAG	VW 505.00
MB	229.52	VAG	VW 505.01
Opel/Vauxhall	OV0401547-D30	VAG	VW 506.00
Opel/Vauxhall	OV0401547-G30	VAG	VW 506.01
PSA	B71 2290	VAG	VW 507.00 Baumuster 2020
PSA	B71 2297		

TYPICAL TECHNICAL PROPERTIES:

Properties	Unit	Method	Typical
SAE Grade		SAE J300	5W/30
Density @15°C	kg/m ³	ASTM D4052	852
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69,8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12,3
Viscosity Index		ASTM D2270	176
Viscosity CCS @-30°, max.	cP	ASTM D5293	5980
Flash Point COC	°C	ASTM D92	224
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.3
Sulphated Ash	%Wt	ASTM D874	0,7

Date Issued: 29-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------