

Product Code: 6226

NORDIC EVOTECH 5W/30 SP

Fully Synthetic Passenger Car Motor Oil

NORDIC EVOTECH 5W/30 SP is an advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol- containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components while meeting the latest GM Dexos1™ demands.

NORDIC EVOTECH 5W/30 SP is based on exceptional quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improved protection against stochastic pre-ignition.
- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection.
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

NORDIC EVOTECH 5W-30 SP exceeds the following performance criteria:

GM Dexos1 TM :2015	ILSAC GF-5	APISN + RC + SP
GM 6094M	GM 4718M	Chrysler MS 6395

Typical Analysis

Properties		Unit	Meth	od	Typical Value
SAE Grade			SAE J3	800	5W/30
Density @15°C		kg/m³	ASTM	D4052	852
Kin. Viscosity @40°C		mm²/s	ASTM	D7042	60
Kin. Viscosity @100°C		mm²/s	ASTM	D7042	10.9
Viscosity Index			ASTM	D2270	174
Viscosity CCS-30°C, max		cР	ASTM	D5293	6600
Flash Point COC		°C	ASTM	D92	>201
Pour Point		°C	ASTM	D97	-42
Total Base Number		mgKOH/g	ASTM	D2896	7.9
Date Issued: 24-04-2021	Supersedes:	Revision Nr.: 1			

Nordic Lube ApS, Udsigten 19, 3500 Vaerleose, Denmark